



House amplifiers

High power amplifiers

- push-pull output stage
- built-in adjustable gain & slope regulators
- die-cast housing
- interstage attenuator and equalizer
- switchable passive or active return path
- input attenuator for active return path
- test points: input - bi-directional, output - directional

HA204

local powered; without return path

HA204R30, HA204R65

local powered; with return path 30 MHz and 65 MHz

HD204

remote powered; without return path

HD204R30, HD204R65

remote powered; with return path 30 MHz and 65 MHz



Technical specifications		HA204	HA204R30	HA204R65	HD204	HD204R30	HD204R65
Type							
Ordering number		10511	10512	10513	10516	10514	10515
Forward path							
Frequency range		47- 862 MHz		87- 862 MHz		47- 862 MHz	87- 862 MHz
Gain*					37 dB		
Gain adjustment					18 dB		
Slope adjustment					18 dB		
Flatness*		±0.5 dB		±0.75 dB		±0.5 dB	±0.75 dB
Input and output return loss					> 14 dB at 40 MHz; -1.5 dB/oct., but not less 10 dB		
Interstage attenuator					-6/0 dB		
Interstage equalizer					-6/0 dB		
Maximal output level CTB, CSO (EN50083-3)**					105 dB μ V		
Noise figure					8 dB		
Test points attenuation					-20 dB		
Return path							
Frequency range	-	5-30 MHz	5-65 MHz	-	5-30 MHz	5-65 MHz	
Gain, switchable	-		27/-4 dB	-		27/-4 dB	
Gain adjustment	-		18 dB	-		18 dB	
Input attenuator	-		-10/0 dB	-		-10/0 dB	
Output equalizer	-		-6/-3/0 dB	-		-6/-3/0 dB	
Flatness	-		±0.75 dB	-		±0.75 dB	
Return loss	-		> 14 dB	-		> 14 dB	
Noise figure	-		7 dB (active, 0 dB attenuator)	-		7 dB (active, 0 dB attenuator)	
Maximal output level IMD3=60 dB (DIN45004B)	-		115 dB μ V (active)	-		115 dB μ V (active)	
General							
Power consumption		230 V~ 50 Hz 7.5 W			24-65 V~ 50 Hz 6.5 W		
Operating temperature range					-20° ÷ +50° C		
Dimensions/Weight (packed)					185x91x47 mm/ 0.68 kg		

* for amplifiers with return path measured 10 MHz after the starting frequency of forward path

** with 6 dB interstage equalizer

