




# 9 cable system Taps and splitter

- 2 way splitter and one way taps of 8 SAT+1 terrestrial signals
- low losses
- switchable DC pass to tap H outputs
- accepts central pin  $\varnothing$  1.2 mm max.

- SS904** 2 way splitter
- SS915** 1 way 15 dB tap
- SS910** 1 way 10 dB tap
- SS920** 1 way 20 dB tap



Technical specifications		SS904	SS910	SS915	SS920
T Y P E					
Ordering number		02710	02711	02712	02713
Frequency range	SAT IF	950-2400 MHz			
	Terr. TV	5-862 MHz			
Through loss	SAT IF	4 dB	1.7 dB	1.2 dB	0.9 dB
	Terr. TV	4 dB	1.6 dB	1.2 dB	1 dB
Tap loss	SAT IF	4 dB	8 ÷ 12 dB	13 ÷ 17 dB	18 ÷ 22 dB
	Terr. TV	4 dB	10 dB	15 dB	20 dB
SAT inputs decoupling	SAT IF	30 dB			
	Terr. TV	30 dB			
DC pass through		2 A max.			
Operating temperature range		-20° ÷ + 50° C			
Dimensions/Weight (packed)		120x120x51 mm/0.4 kg			



# 4 way splitter

- 4 way splitter of 8 SAT+1 terrestrial TV signals
- switchable DC pass to tap H outputs
- accepts central pin  $\varnothing$  1.2 mm max.



Technical specifications		SSQ908
T Y P E		
Ordering number		02714
Frequency range	SAT IF	950-2400 MHz
	Terr. TV	5-862 MHz
Through loss	SAT IF	8 dB
	Terr. TV	8 dB
SAT inputs decoupling	SAT IF	30 dB
	Terr. TV	30 dB
DC pass through		2 A max.
Operating temperature range		-20° ÷ + 50° C
Dimensions/Weight (packed)		254x120x51 mm/0.8 kg

