




- Designed for Complementary Use with BDX34, BDX34A, BDX34B, BDX34C and BDX34D
- 70 W at 25°C Case Temperature
- 10 A Continuous Collector Current
- Minimum h_{FE} of 750 at 3V, 3 A

TO-220 PACKAGE
(TOP VIEW)



Pin 2 is in electrical contact with the mounting base.

MDTRACA

absolute maximum ratings at 25°C case temperature (unless otherwise noted)

| RATING | | SYMBOL | VALUE | UNIT |
|--|--------|-----------|-------------|------|
| Collector-base voltage ($I_E = 0$) | BDX33 | V_{CBO} | 45 | V |
| | BDX33A | | 60 | |
| | BDX33B | | 80 | |
| | BDX33C | | 100 | |
| | BDX33D | | 120 | |
| Collector-emitter voltage ($I_B = 0$) | BDX33 | V_{CEO} | 45 | V |
| | BDX33A | | 60 | |
| | BDX33B | | 80 | |
| | BDX33C | | 100 | |
| | BDX33D | | 120 | |
| Emitter-base voltage | | V_{EBO} | 5 | V |
| Continuous collector current | | I_C | 10 | A |
| Continuous base current | | I_B | 0.3 | A |
| Continuous device dissipation at (or below) 25°C case temperature (see Note 1) | | P_{tot} | 70 | W |
| Continuous device dissipation at (or below) 25°C free air temperature (see Note 2) | | P_{tot} | 2 | W |
| Operating free air temperature range | | T_J | -65 to +150 | °C |
| Storage temperature range | | T_{stg} | -65 to +150 | °C |
| Operating free-air temperature range | | T_A | -65 to +150 | °C |

NOTES: 1. Derate linearly to 150°C case temperature at the rate of 0.56 W/°C.
2. Derate linearly to 150°C free air temperature at the rate of 16 mW/°C.

PRODUCT INFORMATION

electrical characteristics at 25°C case temperature (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | | | MIN | TYP | MAX | UNIT |
|--|-------------------------|---------------------|---------------------------|--------|-----|-----|------|
| $V_{(BR)CEO}$ Collector-emitter breakdown voltage | $I_C = 100 \text{ mA}$ | $I_B = 0$ | (see Note 3) | BDX33 | 45 | | V |
| | | | | BDX33A | 60 | | |
| | | | | BDX33B | 80 | | |
| | | | | BDX33C | 100 | | |
| | | | | BDX33D | 120 | | |
| I_{CEO} Collector-emitter cut-off current | $V_{CE} = 30 \text{ V}$ | $I_B = 0$ | $T_C = 100^\circ\text{C}$ | BDX33 | | 0.5 | mA |
| | | | | BDX33A | | 0.5 | |
| | | | | BDX33B | | 0.5 | |
| | | | | BDX33C | | 0.5 | |
| | | | | BDX33D | | 0.5 | |
| | | | | BDX33 | | 10 | |
| | | | | BDX33A | | 10 | |
| | | | | BDX33B | | 10 | |
| | | | | BDX33C | | 10 | |
| | | | | BDX33D | | 10 | |
| I_{CBO} Collector cut-off current | $V_{CB} = 45 \text{ V}$ | $I_E = 0$ | $T_C = 100^\circ\text{C}$ | BDX33 | | 1 | mA |
| | | | | BDX33A | | 1 | |
| | | | | BDX33B | | 1 | |
| | | | | BDX33C | | 1 | |
| | | | | BDX33D | | 1 | |
| | | | | BDX33 | | 5 | |
| | | | | BDX33A | | 5 | |
| | | | | BDX33B | | 5 | |
| | | | | BDX33C | | 5 | |
| | | | | BDX33D | | 5 | |
| I_{EBO} Emitter cut-off current | $V_{EB} = 5 \text{ V}$ | $I_C = 0$ | | | | 10 | mA |
| h_{FE} Forward current transfer ratio | $V_{CE} = 3 \text{ V}$ | $I_C = 4 \text{ A}$ | (see Notes 3 and 4) | BDX33 | 750 | | |
| | | | | BDX33A | 750 | | |
| | | | | BDX33B | 750 | | |
| | | | | BDX33C | 750 | | |
| | | | | BDX33D | 750 | | |
| $V_{BE(on)}$ Base-emitter voltage | $V_{CE} = 3 \text{ V}$ | $I_C = 4 \text{ A}$ | (see Notes 3 and 4) | BDX33 | | 2.5 | V |
| | | | | BDX33A | | 2.5 | |
| | | | | BDX33B | | 2.5 | |
| | | | | BDX33C | | 2.5 | |
| | | | | BDX33D | | 2.5 | |
| $V_{CE(sat)}$ Collector-emitter saturation voltage | $I_B = 8 \text{ mA}$ | $I_C = 4 \text{ A}$ | (see Notes 3 and 4) | BDX33 | | 2.5 | V |
| | | | | BDX33A | | 2.5 | |
| | | | | BDX33B | | 2.5 | |
| | | | | BDX33C | | 2.5 | |
| | | | | BDX33D | | 2.5 | |
| V_{EC} Parallel diode forward voltage | $I_E = 8 \text{ A}$ | $I_B = 0$ | | | | 4 | V |

NOTES: 3. These parameters must be measured using pulse techniques, $t_p = 300 \mu\text{s}$, duty cycle $\leq 2\%$.

4. These parameters must be measured using voltage-sensing contacts, separate from the current carrying contacts.

PRODUCT INFORMATION



thermal characteristics

| PARAMETER | | MIN | TYP | MAX | UNIT |
|-----------------|---|-----|-----|------|------|
| $R_{\theta JC}$ | Junction to case thermal resistance | | | 1.78 | °C/W |
| $R_{\theta JA}$ | Junction to free air thermal resistance | | | 62.5 | °C/W |

resistive-load-switching characteristics at 25°C case temperature

| PARAMETER | TEST CONDITIONS † | | | MIN | TYP | MAX | UNIT |
|-------------------------|-------------------------------|----------------------------|--------------------------------------|-----|-----|-----|---------------|
| t_{on} Turn-on time | $I_C = 3\text{ A}$ | $I_{B(on)} = 12\text{ mA}$ | $I_{B(off)} = -12\text{ mA}$ | | 1 | | μs |
| t_{off} Turn-off time | $V_{BE(off)} = -3.5\text{ V}$ | $R_L = 10\ \Omega$ | $t_p = 20\ \mu\text{s}, dc \leq 2\%$ | | 5 | | μs |

† Voltage and current values shown are nominal; exact values vary slightly with transistor parameters.

PRODUCT INFORMATION

TYPICAL CHARACTERISTICS

TYPICAL DC CURRENT GAIN
VS
COLLECTOR CURRENT




Figure 1.

COLLECTOR-EMITTER SATURATION VOLTAGE
VS
COLLECTOR CURRENT




Figure 2.

BASE-EMITTER SATURATION VOLTAGE
VS
COLLECTOR CURRENT




Figure 3.

PRODUCT INFORMATION

THERMAL INFORMATION

**MAXIMUM POWER DISSIPATION
vs
CASE TEMPERATURE**




Figure 4.

PRODUCT INFORMATION