

Features

- Small size
- SMT-compatible
- Easily formed leads
- Sputtered ruthenium contacts
- Hermetically sealed contacts
- Fast switching speed — up to 500Hz
- Wide range of available magnetic sensitivities

Description

Clare's Mini-DYAD™ dry reed switches are ideally suited for small switching signal applications. This switch has sputtered ruthenium contacts and an extraordinary seal strength, achieved by a patented laser sealing of the glass. In low level or dry switching environments, both switches typically provide >1 billion operations. The switches have hermetically sealed contacts and offer a wide range of available magnetic sensitivities.

Applications

- Security
- Proximity sensing
- Smoke alarms
- Automotive
 - Level sensor
 - Lamp current sensor
- Relays

Ordering Information

A complete part number is represented by the digits to the right. For example, MN2S1030 is a MINI-DYAD™ with a minimum operate value of 10 and a maximum of 30. Refer to the switch operating specification charts for available ranges. Special ranges are available upon request.



Surface Mount Mini-Dyad

Refer to operating characteristics table for complete part number.

Mini-DYAD™

Part #	Operate Range (NI) ¹
MN2S1015	10 to 15
MN2S1020	10 to 20
MN2S1030	10 to 30
MN2S1520	15 to 20
MN2S1525	15 to 25
MN2S2025	20 to 25

Mini-DYAD™ Surface Mount

Part #	Operate Range (NI) ^{1,2,3}
MN2308	10 to 15
MN2288	10 to 20
MN2339	10 to 30
MN2285	15 to 20
MN2289	15 to 25
MN2286	20 to 25

¹ Tolerance = ± 1.5NI

² Full Blade Sensitivity

³ Surface Mount Switches are packaged 2,000 parts per reel

Approvals

- UL listed

Standard Test Coil

The magnetic force (expressed in NI, AT or Ampere Turns) required to cause the reed switch contacts to close is called the pull-in or operate value.

	MN2
Part #	Coil - 1
Coil definition	NARM1 CTC01
Coil resistance	1200Ω
Number of turns	5,000
Wire size (nom. diameter)	0.0399mm (AWG 46)
Bobbin diameter (inside coil)	3.96mm
Winding length	10.4mm

¹ Consult factory for test procedure.

The reed switch shall be placed in the test coil with the gap centered in the core of the coil winding. Test leads and their clips must be non-magnetic.

The longitudinal axis of the test coil and the test switch shall be vertical.

Mini-Dyad™

MN2

Ratings (@ 25° C)

Parameter	Min	Typ	Max	Units
Switching Voltage MN2 - Mini-DYAD™	-	-	200	Volts
Switching Current MN2 - Mini-DYAD™	-	-	0.5	Amps
Carry Current MN2 - Mini-DYAD™	-	-	2	Amps
Switching Frequency MN2 - Mini-DYAD™	-	-	500	Hz
Contact Resistance MN2 - Mini-DYAD™	-	-0	100	mΩ

(See detailed specifications for more information.)

Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this data sheet is not implied. Exposure of the device to the absolute maximum ratings for extended period may degrade the device and effect its reliability.

Specifications

All parameters are at 25°C unless otherwise stated.

PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNITS
Contact Ratings						
Operate ampere turns range	Full Blade Tolerance = ± 1.5NI	AT	10	-	25	NI
Release ampere turns range	Full Blade Tolerance = ± 1.5NI	AT	5	-	25	NI
Switching Voltage	Max DC/PeakAC Resistive	V _L	-	-	200	VDC
Switching Current	Max DC/PeakAC Resistive	I _L	-	-	500	mAmps
Carry Current	Max DC/PeakAC Resistive	I _C	-	-	2.0	Amps
Contact Rating	Max DC/PeakAC Resistive	-	-	-	10	VA
Life Expectancy	1V, 10mA Signal Level	-	-	1000	-	x10 ⁶ Ops
	10V, 10mA Low Level	-	-	500	-	x10 ⁶ Ops
	50V, 100mA Telecom Load	-	-	2	-	x10 ⁶ Ops
	100V, 100mA Rated Loads	-	-	2	-	x10 ⁶ Ops
Static Contact Resistance	50mV, 10mA ⁽¹⁾	CR	-	70	100	Ω
Contact Material	-	-	-	R _u	-	-
Switch Specifications						
Insulation Resistance ⁽²⁾	100V, 25°C, 40% RH	IR	10 ⁸	10 ¹¹	-	Ω
Capacitance	Across Open Contacts	-	-	0.3	-	pF
Dielectric Strength ⁽³⁾	Between Contacts	-	250	300	-	VDC/Peak AC
Operate Time, including bounce	At nominal coil voltage, 10Hz Square Wave	T _{OP}	-	-	0.5	ms
Release Time	Zener-Diode Suppression ⁽⁴⁾	T _{RP}	-	-	0.1	ms
Environmental Ratings						
Storage Temperature	-	T _A	-40	-	+125	°C
Operating Temperature	-	T _O	-40	-	+125	°C
Soldering Temperature	-	-	-	-	+265	°C
Vibration Resistance	5Hz - 200Hz	G	-	-	20	-Gs
Shock Resistance	11±1ms, 1/2 Sine Wave	S	-	-	50	Gs
Weight	-	-	-	0.12	-	grams/unit

⁽¹⁾ Contact resistance measured with 4 terminal method, 1.1' between test leads

⁽²⁾ >10⁸ Ω is available upon request





⁽³⁾ A 24V zener in series with a diode across the coil

⁽⁴⁾ Use caution not to exceed vibration resistance limits while ultrasonically cleaning. Contact CP Clare Engineering for more details/ recommendations

⁽⁵⁾ 15 ampere turn minimum

Performance Data*


Mini-DYAD™




*The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.

Mechanical Dimensions

Mini-DYAD™



Mini-DYAD™ SMT



Recommended Pad Sizes

Mini Dyad™ SMT




Dimensions
mm
(inches)

Mini-Dyad™

MN2

Tape & Reel Packaging

Tape and Reel Packaging for SMT CM10 Switch



Dimensions
mm
inches