




Single secondary version

Primary: pins 1 - 5
Secondary: pins 7 - 9



Double secondary version

Primary: pins 1 - 5
Secondary 1: pins 6 - 7
Secondary 2: pins 9 - 10



MAIN FEATURES:

- Unitary insulation test at **5KV**
- According **EN61558** European Standard (CE)
- All used materials are minimum **Class B** (130°C)
- Protection index: **IP00**
- Weight: **160gr**
- **Other voltages or pin-out under request**

| JESIVA Part n° | RATED POWER | PRIMARY | SECONDARY | TEMP | Recommended FUSE |
|----------------|-------------|---------|------------------|--------|------------------|
| E3814.35.1.06 | 3.5VA | 230V | 6V / 0.58A | 70°C/B | Prim. 32mA/T |
| E3814.35.1.07 | 3.5VA | 230V | 7.5V / 0.46A | 70°C/B | Prim. 32mA/T |
| E3814.35.1.09 | 3.5VA | 230V | 9V / 0.38A | 70°C/B | Prim. 32mA/T |
| E3814.35.1.12 | 3.5VA | 230V | 12V / 0.29A | 70°C/B | Prim. 32mA/T |
| E3814.35.1.15 | 3.5VA | 230V | 15V / 0.23A | 70°C/B | Prim. 32mA/T |
| E3814.35.1.18 | 3.5VA | 230V | 18V / 0.19A | 70°C/B | Prim. 32mA/T |
| E3814.35.1.24 | 3.5VA | 230V | 24V / 0.14A | 70°C/B | Prim. 32mA/T |
| E3814.35.2.06 | 3.5VA | 230V | 2x6V / 2x0.29A | 70°C/B | Sec. 2x315mA/F |
| E3814.35.2.07 | 3.5VA | 230V | 2x7.5V / 2x0.23A | 70°C/B | Sec. 2x250mA/F |
| E3814.35.2.09 | 3.5VA | 230V | 2x9V / 2x0.19A | 70°C/B | Sec. 2x200mA/F |
| E3814.35.2.12 | 3.5VA | 230V | 2x12V / 2x0.14A | 70°C/B | Sec. 2x160mA/F |
| E3814.35.2.15 | 3.5VA | 230V | 2x15V / 2x0.11A | 70°C/B | Sec. 2x125mA/F |
| E3814.35.2.18 | 3.5VA | 230V | 2x18V / 2x0.097A | 70°C/B | Sec. 2x100mA/F |
| E3814.35.2.24* | 3.5VA | 230V | 2x24V / 2x0.073A | 70°C/B | Sec. 2x80mA/F |

DATA SHEET

EI38/14

Encapsulated transformer

JESIVA 
transformers

Code:

E3814.35.X.XX

Date:

Dec 2011

www.JESIVA.com