

Hochleistungsfette

H1 (FDA 21 CFR)

Risk group P2

Silicone Grease





Special lubricant for valves, fittings and seals | drinking water approval | NSF registration | BAM

WEICON Silicone Grease is strong, transparent and shows very good compatibility to plastics. Due to its NSF H1 registration, WEICON Silicone Grease is suitable as lubricant in sensitive areas where inadvertent contact to food is possible. Complies with the Guideline for Hygienic Assessment of Organic Materials in Contact with Drinking Water (KTW Guideline) by the Federal Environment Agency. It can be used in the food and beverage industry, in sanitary and heating construction, in the pharmaceutical industry as well as in the sealing technology. WEICON Silicone Grease is BAM safety-tested - see leaflet 034-1 "List of non-metallic materials for use in oxygen" (DGUV information 213-075) of BG RCI. The grease is particularly material-friendly, neutral in odour and taste and has a temperature resistance of -50°C to +200°C.

WEICON Silicone Grease is suitable for the lubrication of plastics, rubber parts and seals, valves, fittings and gaskets, machines, equipment, slow rotating bearings and as assembly aid for O-rings.

Technical Data

Consistency classification	DIN 51818	NLGI grade 2-3
Base		Pyrogenic silicon dioxide silicone oil
Colour		colourless, translucent
Density	(+20°C) DIN 51757	0,98 g/cm ³
Cone penetration	DIN ISO 2137	222 - 310 1/10 mm
Heat capacity	DIN EN ISO 22007-4	1,295 J/(g·K)
Thermal conductivity		0,445 W/m·K
Dielectric strength	DIN EN 60243-1 (20°C)	9,2 kV/mm
EMCOR-corrosion test	DIN 51 802	1/2
Temperature conductivity		0,351 mm ² /s
Temperature resistance		-50°C to +200°C
Shelf life		24 mon.
Approvals / Guidelines		

Lubricating and Multifunctional Oils

Hygiene Institute

Surface pre-treatment Clean surfaces.

NSF

Processing

Apply Silicone Grease evenly.

Shelf life

Store in tightly closed original container. Do not store with oxidising agents. Keep container tightly closed and store in a cool, well-ventilated area. Recommended storage temperature:. Room temperature.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our safety data sheets (www.weicon.com) must be observed.

Available sizes:

26350005	Silicone Grease, 5 g, colourless, translucent
26350085	Silicone Grease, 85 g, colourless, translucent
26350045	Silicone Grease, 0,45 kg, colourless, translucent

Conversion table

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.