

Distributed by:



www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

DC FAN

JAMICON®

60X60X25 (A) mm

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%



SPECIFICATIONS

Model	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (mmH ₂ O)	Speed (R.P.M)	Rated Current (Amp)	Input Power (Watt)	Noise (dBA)	Weight (g)
JF0625x1TR	12	10.2 ~ 13.8	29.69	10.73	6000	0.41	4.92	42.5	65.0
JF0625x1UR			26.96	9.06	5500	0.35	4.20	39.2	
JF0625x1SR			24.27	7.42	5000	0.29	3.48	35.7	
JF0625x1H			21.44	6.03	4500	0.23	2.76	34.1	
JF0625x1M			19.00	4.69	4000	0.20	2.40	31.6	
JF0625x1L			16.76	3.68	3500	0.17	2.04	27.3	
JF0625x1E			14.24	2.74	3000	0.13	1.56	21.8	
JF0625x1V			11.72	1.93	2500	0.08	0.96	20.2	
JF0625x2TR	24	20.4 ~ 27.6	29.69	10.73	6000	0.25	6.00	42.5	
JF0625x2UR			26.96	9.06	5500	0.22	5.28	39.2	
JF0625x2SR			24.27	7.42	5000	0.19	4.56	35.7	
JF0625x2H			21.44	6.03	4500	0.17	4.08	34.1	
JF0625x2M			19.00	4.69	4000	0.13	3.12	31.6	
JF0625x2L			16.76	3.68	3500	0.11	2.64	27.3	
JF0625x2E			14.24	2.74	3000	0.09	2.16	21.8	
JF0625x2V			11.72	1.93	2500	0.07	1.68	20.2	
JF0625x4T	48	40.8 ~ 55.2	29.69	10.73	6000	0.16	7.68	42.5	
JF0625x4U			26.96	9.06	5500	0.14	6.72	39.2	
JF0625x4S			24.27	7.42	5000	0.12	5.76	35.7	
JF0625x4H			21.44	6.03	4500	0.10	4.80	34.1	
JF0625x4M			19.00	4.69	4000	0.08	3.84	31.6	
JF0625x4L			16.76	3.68	3500	0.06	2.88	27.3	
JF0625x4E			14.24	2.74	3000	0.05	2.40	21.8	

P.S.: The 7th character of the model codes could be "S", "C" or "B"; "S": Sleeve bearing, "C": Ball + Sleeve bearing, "B": Two ball bearing
 Specifications subject to change without notice

