

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%



### SPECIFICATIONS

| Model        | Bearing | Rated Voltage (V) | Operating Voltage (V) | Air Flow (CFM) | Static Pressure (inchH <sub>2</sub> O) | Speed (R.P.M.) | Input Current (Amp) | Input Power (Watt) | Nominal Current (Amp) | Noise (dBA) | Weight (g) |
|--------------|---------|-------------------|-----------------------|----------------|----------------------------------------|----------------|---------------------|--------------------|-----------------------|-------------|------------|
| JF1238B1TRAD | B       | 12                | 10.2 ~ 13.8           | 180.72         | 0.67                                   | 4400           | 1.46                | 17.52              | 1.50                  | 56.20       | 307        |
| JF1238B1TR   |         |                   |                       | 163.86         | 0.63                                   | 4000           | 1.33                | 15.96              | 1.50                  | 52.90       |            |
| JF1238B1UR   |         |                   |                       | 144.13         | 0.50                                   | 3600           | 0.96                | 11.52              | 1.00                  | 50.70       |            |
| JF1238B1SR   |         |                   |                       | 127.47         | 0.41                                   | 3200           | 0.76                | 9.12               | 0.80                  | 46.70       |            |
| JF1238B1HR   |         |                   |                       | 110.59         | 0.32                                   | 2800           | 0.50                | 0.60               | 0.55                  | 43.50       |            |
| JF1238B1MR   |         |                   |                       | 93.97          | 0.24                                   | 2400           | 0.35                | 4.20               | 0.38                  | 40.20       |            |
| JF1238B1LR   |         |                   |                       | 79.96          | 0.18                                   | 2000           | 0.19                | 2.28               | 0.21                  | 34.10       |            |
| JF1238B1ER   |         |                   |                       | 68.19          | 0.13                                   | 1700           | 0.10                | 1.20               | 0.11                  | 28.60       |            |
| JF1238B2TR   | B       | 24                | 20.4 ~ 27.6           | 163.86</       |                                        |                |                     |                    |                       |             |            |