

40X40X10 mm

KF0410-03 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

SPECIFICATIONS												
Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)	
KF0410B5H-03	Dual Ball	5	4.25~5.75	6.42	0.129	6000	0.13	0.65	0.8	26.4	15	
KF0410B5M-03				5.75	0.106	5400	0.09	0.45	0.5	24.4		
KF0410B5L-03				4.37	0.067	4200	0.07	0.35	0.4	19.9		
KF0410S5H-03	Sleeve			6.42	0.129	6000	0.20	1.00	1.2	26.4		
KF0410S5M-03				5.75	0.106	5400	0.10	0.50	0.8	24.4		
KF0410S5L-03				4.37	0.067	4200	0.08	0.40	0.6	19.9		
KF0410B1H-03	Dual Ball	12	10.2~13.8	6.42	0.129	6000	0.07	0.84	0.8	26.4		
KF0410B1M-03				5.75	0.106	5400	0.06	0.72	0.7	24.4		
KF0410B1L-03				4.37	0.067	4200	0.05	0.60	0.6	19.9		
KF0410S1H-03	Sleeve			6.42	0.129	6000	0.08	0.96	1.2	26.4		
KF0410S1M-03				5.75	0.106	5400	0.07	0.84	0.8	24.4		
KF0410S1L-03				4.37	0.067	4200	0.06	0.72	0.7	19.9		
KF0410B2S-03	Dual Ball	24	20.4~27.6	6.97	0.159	6600	0.06	1.44	1.4	29.3		
KF0410B2H-03				6.42	0.129	6000	0.05	1.20	1.2	26.4		
KF0410B2M-03				5.75	0.106	5400	0.04	0.96	1.0	24.4		
KF0410B2L-03				4.37	0.067	4200	0.03	0.72	0.8	19.9		
KF0410S2H-03				Sleeve	6.42	0.129	6000	0.05	1.20	1.2		26.4
KF0410S2M-03					5.75	0.106	5400	0.04	0.96	1.0		24.4
KF0410S2L-03	4.37	0.067	4200	0.03	0.72	0.8	19.9					

Specifications subject to change without notice

